

M'SOFT FREEZ OV - S2



Suitable for :	Inside
Type :	Low shoe
Activity :	Food industry, Catering, Medical / Chemical Industry / Electronic Industry, ESD
Upper :	Dry-Tek® material, thickness 2.2 mm, acid resistant, washable and breathable
Lining :	Artico® "Refreshing" treatment with integrated scented microcapsules
Tongue :	Dry-Tek® material
Ankle protection :	
Fastening :	Elastic closure on the instep
Toe cap :	Ultralight and extra wide Composite 200 joules Light System®
Midsole :	
Insole :	Thermoformed, anatomical, foam dual density, activated carbon, antistatic and antibacterial
Sole :	PU 2D exclusive SOFT SYSTEM® platform, antistatic, HI-CI, ESD treatment
Sole pattern :	Special non-slip gripping on smooth and greasy floors, SRC standard
Weight (Kg/pair) :	0.910
Colors :	White and grey upper and white/light grey outsole
Sizes :	35-48 (2-13)
Standard :	EN ISO 20345:2011 SRC / EN 61340-4-3 / DGVU 112-191
CE certificate of conformity N° :	0075/020/161/03/18/0511 - EXT 28/08/18
Special features :	Overcap reinforcement by R-PU injection method, high abrasion and impact resistance
Special features 2 :	Upper without side stitching: no water infiltration risks, washable up to 60°C
Special features 3 :	Dry-Tek® material resistant to 12 acids and corrosive fluids (standard EN 13832-2)

SPECIAL FEATURES

- 200 joules light composite toecap
- Metal free, non magnetic
- Water absorption and penetration resistance of upper (WRU)
- Electro Static Discharge Standard EN 61340-5-1



GENERAL FEATURES

- Antistatic properties (A)
- Heel energy absorption (E)
- Abrasion resistance
- Crampon sole
- Heat-insulated sole (HI)
- Cold-insulated sole (CI)
- 200 joule extra-wide toecap
- Hyper-ventilated lining
- Perforation-resistance 1100 N (P)